



# FLAP WHEELS



## Flap Wheels

CUMI's flange mounted large dia. Flap wheels are widely used for blending, de-burring and finishing OD of SS tubes, pipes, Utensils and auto components. The abrasive is non-loading, non-dulling due to nature of evenly wearing out flaps. This results in consistent finish. Adhesive used is uniformly distributed and ensures strong bonding and minimum vibration during use.

### HI-CUT

#### Product Description

Aluminium Oxide flap wheels designed for good cutting action throughout wheel life.

#### Product Features

- Aluminium Oxide grain uniformly coated on X' wt. Cotton backing for consistent finish
- Universal design for easy mounting
- Good adhesion for high surface speed
- Available in various sizes to suit typical applications



Abrasive Used	Grit	Dia (mm)	Thick (mm)	Bore (mm)	Best Suited for
XG 542	36, 60, 80, 100, 120, 150, 180, 220, 320, 400, 600, 800, 1000, 1200	250, 300, 350	25, 40, 50	181, 127.5	Stainless steel, MS, Alloys

### JAWAN

#### Product Description

Aluminium Oxide flap wheels designed for flexible operation with superior finish.

#### Product Features

- Aluminium Oxide grain uniformly coated on X' wt. Cotton backing for controlled cutting action
- Provides higher flexibility while operation
- Uniform cutting throughout wheel life



Abrasive Used	Grit	Dia (mm)	Thick (mm)	Flange Bore (mm)	Best Suited for
XG 542	36, 60, 80, 100, 120, 150, 180, 220, 320, 400, 600, 800, 1000, 1200	250, 300, 350	25, 50	91, 114, 154	Stainless steel, MS, Alloys

*\*Note: Non standard sizes available on request*